

In the claims:

Please cancel claim 15 from consideration herein, the limitations of which have been incorporated into claim 12, and add new claims 16 and 17. A complete listing of all claims, and their status, is included.

1. (Currently Amended) A discharge lamp assembly comprising:

a discharge light source;

a reflector operatively associated with the light source for directing light from the light source in a desired manner, the reflector including pre-formed openings for venting therethrough; and

a foraminous containment structure [including discrete panels dispose] disposed in spaced, overlying relation with the respective reflector openings and formed to wrap around a periphery of the reflector.

2. (Currently Amended) The discharge lamp assembly of claim 1 wherein the containment strucure includes discrete panels that are interconnected by a structural member.

3. (Original) The discharge lamp assembly of claim 2 wherein the structural member is a wire.

4. (Original) The discharge lamp assembly of claim 1 wherein the reflector pre-formed openings are recesses extending axially inward from a first end of the reflector.

5. (Original) The discharge lamp assembly of claim 4 wherein the recesses are spaced about a perimeter of the first end.

BEST AVAILABLE COPY

6. (Currently Amended) The discharge lamp assembly of claim 1 further comprising a cage that receives the reflector therein, the containment [assembly] structure securing the reflector to the cage.

7. (Currently Amended) The discharge assembly of claim 1 wherein the containment [assembly] structure includes a support wire and individual panels secured to the wire.

8. (Currently Amended) A discharge lamp assembly having improved venting and recycling features, the lamp assembly comprising:

a discharge light source;

a reflector operatively associated with the light source for directing light from the light source in a desired manner, the reflector including pre-formed openings for venting therethrough; and

[discrete panels dispose] a separate containment structure from the light source and the reflector disposed in spaced, overlying relation with the respective reflector openings and [adhesively] secured to the reflector.

9. (Original) The discharge assembly of claim 8 wherein the reflector pre-formed openings are recesses extending axially inward from a first end of the reflector.

10. (Original) The discharge lamp assembly of claim 9 wherein the recesses are spaced about a perimeter of the first end.

11. (Currently Amended) The discharge lamp assembly of claim 8 further comprising a cage that receives the reflector therein, the containment [assembly] structure securing the reflector to the cage.

BEST AVAILABLE COPY

12. (Currently Amended) A discharge lamp assembly comprising:
a discharge light source;
a reflector operatively associated with the light source for directing light from the
light source in a desired manner, the reflector including pre-formed openings for venting
therethrough; [and]
a [basket-like] containment assembly dimensioned for receipt within the reflector
and circumferentially surrounding the light source; and
a cage that receives the reflector therein, the containment assembly securing the
reflector to the cage.

13. (Original) The discharge assembly of claim 12 wherein the reflector pre-formed
openings are recesses extending axially inward from a first end of the reflector.

14. (Original) The discharge lamp assembly of claim 13 wherein the recesses are spaced
about a perimeter of the first end.

15. (Canceled).

16. (New) The discharge lamp assembly of claim 1 wherein the containment structure
includes discrete panels disposed in the spaced, overlying relation with the respective reflector
openings.

17. (New) The discharge lamp assembly of claim 8 wherein the containment structure
includes discrete panels disposed in the spaced, overlying relation with the respective reflector
openings.

BEST AVAILABLE COPY